[Lead2pass New Free Download 300-101 Exam Dumps VCE From Lead2pass (221-240)

2017 October Cisco Official New Released 300-101 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! 300-101 dumps free share: Lead2pass presents the highest quality of 300-101 exam dump which helps candidates to pass the 300-101 exams in the first attempt. Following questions and answers are all new published by Cisco Official Exam Center: https://www.lead2pass.com/300-101.html QUESTION 221An engineer is using a network sniffer to troubleshoot DHCPv6 between a router and hosts on the LAN with the following configuration: Interface Ethernet Olpv 6 dhcp server DHCPSERVERPOOL rapid-commit! Which two DHCPv6 messages will appear in the snifer logs? A. replyB. requestC. advertiseD. acknowledgeE. acceptAnswer: AEExplanation: The Rapid Commit option is used to indicate the use of the two- message exchange for address assignment. The code for the Rapid Commit option is 80. The format of the option is:Code Len+----+ | 80 | 0 | +----+A client MUST include this option in a DHCPDISCOVER message if the client is prepared to perform the DHCPDISCOVER-DHCPACK message exchange described earlier. A server MUST include this option in a DHCPACK message sent in a response to a DHCPDISCOVER message when completing the DHCPDISCOVER- message exchange.DHCPACK QUESTION 222Drag and Drop Question Answer: QUESTION 223Drag and Drop Question Answer: QUESTION 224Drag and Drop Question Answer: QUESTION 225Drag and Drop Question Answer: QUESTION 226Drag and Drop QuestionDrag and drop the challenge Handshake Authentication Protocol steps from the left into the correct order in which they occur on the right. Answer: QUESTION 227Which BGP option is required when load sharing over multiple equal-bandwidth parallel links from a single CE router to a single ISP router over eBGP? Select the best response. A. eBGP MultipathB. eBGP MultihopC. BGP SynchronizationD. Public AS numbers Answer: B QUESTION 228Which statement is true about EBGP? Select the best response. A. An internal routing protocol can be used to reach an EBGP neighbor.B. The next hop does not change when BGP updates are exchanged between EBGP neighbors.C. A static route can be used to form an adjacency between neighbors.D. EBGP requires a full mesh. Answer: CExplanation: When BGP is running between routers in different autonomous systems, it is called External BGP (EBGP). When BGP is running between routers in the same AS, it is called Internal BGP (IBGP). BGP allows the path that packets take to be manipulated by the AS, as described in this module. It is important to understand how BGP works to avoid creating problems for your AS as a result of running BGP. QUESTION 229Which two statements are true of the OSPF link-state routing protocol? (Choose two.) A. Using the Bellman-Ford algorithm, each OSPF router independently calculates its best paths to all destinations in the network.B. Using the DUAL algorithm, each OSPF router independently calculates its best paths to all destinations in the network.C. OSPF sends summaries of individual link-state entries every 30 minutes to ensure LSDB synchronization.D. OSPF sends triggered updates when a network change occurs. E. OSPF sends updates every 10 seconds.F. When a link changes state, the router that detected the change creates a link-state advertisement (LSA) and propagates it to all OSPF devices using the 224.0.0.6 multicast address. Answer: CDExplanation: The point of this question is the basis of OSPF. Incorrect answer A. OSPF send hello packets every 10 seconds, not the updates, OSPF sends triggered updates when a network change occurs. For OSPF, D Rother use the multicast address 224.0.0.6 to send packets to DR and BDR, only DR and BDR can get the information from this multicast address. QUESTION 230Your network consists of a large hub-and-spoke Frame Relay network with a CIR of 56 kb/s for each spoke. Which statement about the selection of a dynamic protocol is true? Select the best response. A. EIGRP would be appropriate if LMI type ANSI is NOT used.B. EIGRP would be appropriate, because the Frame Relay spokes could be segmented into their own areas.C. EIGRP would be appropriate, because by default, queries are not propagated across the slow speed Frame Relay links.D. EIGRP would be appropriate, because you can manage how much bandwidth is consumed over the Frame Relay interface. Answer: DExplanation: By default, EIGRP will limit itself to using no more than 50% of the interface bandwidth. The primary benefit of controlling EIGRP's bandwidth usage is to avoid losing EIGRP packets, which could occur when EIGRP generates data faster than the interface line can absorb it. This is of particular benefit on Frame Relay networks, where the access interface bandwidth and the PVC capacity may be very different. QUESTION 231Refer to exhibit. What is indicated by the show ip cef command for an address? A. CEF is unable to get routing information for this route.B. CEF cannot switch packet for this route and passes it to the next best switching method.C. A valid entry and is pointed to hardware based forwarding.D. CEF cannot switch packet for this route and drops it. Answer: BExplanation: Glean adjacency ­ in short when the router is directly connected to hosts the FIB table on the router will maintain a prefix for the subnet rather than for the individual host prefix. This subnet prefix points to a GLEAN adjacency. Punt adjacency ­ When packets to a destination prefix can't be CEF Switched, or the feature is not supported in the CEF Switching path, the router will then use the next slower switching mechanism configured on the router. QUESTION 232Refer to Exhibit. Which two reasons for IP SLA tracking failure are likely true? (Choose

Two) A. The source-interface is configured incorrectly.B. The destination must be 172.30.30.2 for icmp-echo.C. A route back to the R1 LAN network is missing in R2.D. The default route has wrong next hop IP address.E. The threshold value is wrong, Answer: AC QUESTION 233A network engineer enables OSPF on a Frame Relay WAN connection to various remote sites, but no OSPF adjacencies come up. Which two actions are possible solutions for this issue? (Choose Two) A. Change the network type to point-to-multipoint under WAN interface.B. Enable virtual links.C. Change the network type to nonbroadcast multipoint access. D. Configure the neighbor command under OSPF process for each remote site.E. Ensure that the OSPF process number matches among all remote sites Answer: AD QUESTION 234A network engineer applies the command ip tcp adjust-mss
 bytes> under interface configuration mode. What is the result? A. The probability of SYN packet truncation is increased.B. The UDP session is inversely affected.C. The probability of dropped or segmented TCP packets is decreased.D. The optimum MTU value for the interface is set. Answer: C QUESTION 235Which command configures a PPPoE client and specifies dial-on-demand routing functionality? A. pppoe-client dial-pool-numberB. PPPoE enable.C. interface dialer 1D. encapsulation PPP Answer: A OUESTION 236Which statement about dual stack is true? A. Dual stack translates IPv6 addresses to IPv4 addresses.B. Dual stack means that devices are able to run IPv4 and IPv6 in parallel.C. Dual stack translates IPv4 addresses to IPv6 addresses.D. Dual stack changes the IP addresses on hosts from IPv4 to IPv6 automatically. Answer: B QUESTION 237Which two OSPF network types can operate without a DR/BDR relationship? (Choose Two) A. Point-to-multipointB. Point-to-pointC. nonbroadcastD. nonbroadcast multi-accessE. broadcast Answer: AB QUESTION 238In a point-to-multipoint Frame Relay topology, which two methods ensure that all routing updates are received by all EIGRP routers within the Frame Relay network? (Choose Two) A. Use statically defined EIGRP neighbors on the hub site.B. Create separate address families.C. Disable split horizon.D. Use subinterfaces.E. Disable EIGRP auto summary. Answer: CD QUESTION 239What following parameters for the EIGRP authentication need to match in order for EIGRP neighbors to establish a neighbor relationship? A. Autonomous System number.B. K-ValuesC. If authentication is used both: the key number, the password, and the date/time.D. The neighbors must be on common subnet (all IGPs follow this rule). Answer: C QUESTION 240A network engineer recently deployed Easy Virtual Networking in the enterprise network. Which feature improves shared services support? A. route replicationB. edge interfacingC. tunnel feedback.D. route distinguishers Answer: A Lead2pass is now offering Lead2pass 300-101 PDF dumps with 100% passing guarantee. Use Lead2pass 300-101 PDF and pass your exam easily. Download Cisco 300-101 exam dumps and prepare for exam. 300-101 new questions on Google Drive: https://drive.google.com/open?id=0B3Syig5i8gpDX0QwYXF1aXFINmM 2017 Cisco 300-101 exam dumps (All 470 Q&As) from Lead2pass: https://www.lead2pass.com/300-101.html [100% Exam Pass Guaranteed]