

[Lead2pass New Free Version Lead2pass Cisco 300-320 PDF Dumps With Exam Questions Download (351-375)]

2017 November Cisco Official New Released 300-320 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed!

We offer the most current and best training materials of the 300-320 certification Q&A , Practice Software, Study Packs, Preparation Labs and Audio Training you are looking for. Our online certification training offers you quick and cost-efficient way to train and become a certified professional in IT industry. Following questions and answers are all new published by Cisco Official Exam

Center: <https://www.lead2pass.com/300-320.html> QUESTION 351When designing data centers for multitenancy, which two benefits are provided by the implementation of VSAN and zoning? (choose two) A. VSAN provides a means of restricting visibility and connectivity among devices connected to a zoneB. VSANs have their own set of services and address space, which prevents an issue in one VSAN from affecting othersC. Zones provide the ability to create many logical SAN fabrics on a single Cisco MDS 9100 family switchD. VSANs and zones use separate fabricsE. Zones allow an administrator to control which initiators can see which targetsAnswer: BE QUESTION 352For which engine an IPS can use its reputation awareness? (Choose two) A. Reputation filteringB. Reputation subscriptionsC. Correlation rulesD. Global correlation inspection Answer: AD

Explanation:http://www.cisco.com/c/en/us/products/collateral/security/ips-4500-series-sensors/white_paper_c11-715386.html

QUESTION 353When designing a layer 2 STP-based LAN with Layer 3 FHRP, which design recommendation should be followed?

A. Avoid modifying default STP and FHRP timers.B. Assign the native VLAN to the lowest number in use.C. Avoid configuring router preemption.D. Align the STP root with the active FHRP device. Answer: D QUESTION 354A company have single ASA hardware box and they need to separate company departments in way that they can apply different rules on them, ACL, NAT, and so on...Which mode is needed? A. routed modeB. transparent modeC. multiple context modeD. active failover mode Answer: C QUESTION 355Engineer is designing QoS for application. Which QoS architecture should he choose if application needs to have reserved bandwidth prior to sending data? A. Differentiated servicesB. Integrated servicesC. LLQD. ToS Answer: B QUESTION 356An engineer chose to design an architecture where distribution switches are in VSS and are connected to access switches using Multichassis Etherchannel. What is the resulting topology? A. LoopedB. RingC. HybridD. Star Answer: D QUESTION 357With which of the following could EIGRP and OSPF achieve sub second convergence ? (Choose Two) A. BFDB. Triangle topologyC. Square topologyD. Ring topologyE. Tuning timersF. IP SLA Answer: AB

QUESTION 358A network designer needs to explain the advantages of route summarization to a client. Which two options are advantages that should be included in the explanation? (Choose Two) A. Increases security by advertising fake networks.B. Reduces routing table size.C. Advertises detailed routing sizeD. Utilizes the routers full CPU capacity.E. Reduces the upstream impact of a flapping interface. Answer: BE QUESTION 359A company is running BGP on the edge with multiple service providers in a primary and secondary role. The company wants to speed up time if a failure were to occur with the primary, but they are concerned about router resources. Which method best achieves this goal? A. Utilize BFD and lower BGP hello intervalB. Decrease the BGP keepalive timerC. Utilize BFD and tune the multiplier to 50D. Utilize BFD and keep the default BGP timers Answer: D QUESTION 360What is one limitation of MPLS Layer 3 VPN networks? A. They require less powerful routers with limited capabilitiesB. They require the customer to control routingC. They support only IP trafficD. PE routers are underutilized Answer: C QUESTION 361If your enterprise is connected to 2 ISP, which method could you use to prevent being used as a transit network? (Choose Two) A. filter outboundB. filter inboundC. throw both ISPD. choose only one ISPE. Allow every routes inbound Answer: AEExplanation:

<https://www.cisco.com/c/en/us/support/docs/ip/border-gateway-protocol-bgp/23675-27.html> QUESTION 362Two company want to merge their OSPF networks, but they run different OSPF domains.Which is option must be created to accomplished this requirement? A. OSPF virtual link to bridge the backbone areas of the two company togetherB. Route SummarizationC. Static OSPFD. Redistribute routes between domains Answer: D QUESTION 363Two Cisco switches with 1 SUP and many 10G line-card ports for each switch, run in VSS mode. In which case or for what reason you don't connect all VSL to SUP? A. The need for hardware diversityB. Bandwidth congestion at SUPC. In case the sup failD. Qos must be configured on both Answer: A QUESTION 364Which two metric are used by EIGRP by default to calculate its cost ? (Choose two) A. BandwidthB. Latency C. MTUD. Load Answer: AB QUESTION 365Which one of these could you implement to sustain a large DDoS attack? A. Stateful firewallB. uRPFC. Connections limits and timeoutsD. Access-lists Answer: C QUESTION 366What QoS technology allows traffic to pass even though it has exceeded the bandwidth limit but will be queued later? A. ShapingB. PolicingC. Weighted Fair QueuingD. Low Latency Queuing Answer: A QUESTION 367A company needs to configure a new firewall and have only one public IP address to use in this firewall.The engineer need to configure the firewall with NAT to handle inbound

traffic to the mail server in addition to internet outbound traffic. Which options could he use ? (Choose Two) A. Static NAT for inbound traffic on port 25B. Dynamic NAT for outbound trafficC. Static NAT for outbound traffic on port 25D. Dynamic NAT for inbound trafficE. NAT overload for outbound trafficF. NAT overload for inbound traffic on port 25 Answer: AE

QUESTION 368During the design of a new data center, a company requires that access switches be placed only in network racks. Which switch layout must be used? A. centralizedB. integratedC. top of rackD. end of row Answer: D

QUESTION 369An engineer have to design a multicast domain for some application. This multicast network should be secured. Which option should he take ? A. ASM with an addressing of 224.0.0.0/8B. ASM with an addressing of 232.0.0.0/8C. SSM with an addressing of 224.0.0.0/8D. SSM with an addressing of 232.0.0.0/8 Answer: D

QUESTION 370HSRP. Router 1 (master) and Router 2 (standby), same priority. When router 1 f0/1 (outside interface) down. With which tracking commands the Router 2 will be able to preempt ? (Choose Two) A. Track 50B. Track 50 decrement 20C. ip tracking 50 interface f0/1 reachabilityD. ip tracking 50 Interface f0/1 ip routing (or line protocol) Answer: BD

QUESTION 371You are assigned the network of 192.168.1.0/24. You want to split the network into four subnets that are all the same size. Which three statements about the first subnet that you create are true? (Choose three.) A. The subnet mask is 255.255.255.192B. The last host IP address is 192.168.1.64C. The subnet mask is 255.255.255.224D. The subnet has up to 64 hostsE. The last host IP address is 192.168.1.62F. The subnet has up to 62 hosts Answer: AEF

QUESTION 372When APIC is down on cluster device. What is the minimum number of APICs requirement for a production ACI Fabric to continue to operate? A. 1B. 2C. 3D. 4 Answer: C

Explanation: From Designing for Cisco Network Service Architecture Fourth Edition: The recommended minimum sizing has the following requirements: * Three or more Cisco APIC controllers that are dual connected to different leaf switches for maximum resilience. Note that the fabric is manageable even with just one controller and operational without a controller.

QUESTION 373Which two elements comprise the backbone area while designing a new network utilizing IS-IS as the interior gateway protocol (choose two) A. contiguous chain of Level 2 capable routersB. contiguous chain of Level 1/Level 2 capable routersC. set of Level 2 configured interfacesD. contiguous Level 1 capable routersE. set of Level 1 configured interfaces Answer: AB

Explanation: https://www.cisco.com/en/US/products/ps6599/products_white_paper09186a00800a3e6f.s.html "Backbone IS-IS does not have a backbone area like the OSPF area 0. The IS-IS backbone is a contiguous collection of Level 2-capable routers, each of which can be in a different area" <http://www.ciscopress.com/articles/article.asp?p=26850&seqNum=3> "In most designs with routing hierarchy, the Level 2 routers are also Level 1 routers by virtue of their identification with a certain area. Therefore, in IS-IS, a router can function as Level 1-only or Level 2-only and possibly as both Level 1 and Level 2 (Level 1-2). Level 1-2 routers act as border routers to their respective areas, providing connectivity to other areas. The Level 2 backbone is essentially a virtual IS-IS area consisting of routers engaged in Level 2 routing"

QUESTION 374About DDOS attack .What you can do on device to block DDOS attack ? A. Policy mapB. ACLC. Control plane policyD. Used zoned firewall on router Answer: C

QUESTION 375An organization is using a link state routing that is not dependent on IP addressing. Which action enable information across area boundaries in this organization ? A. Assign level 1 router interfaceB. Assign level 1 routers to different areasC. Assign level 2 router interface to the backbone areaD. Assign level 2 router to different areasE. Assign level 2 router interface to different area Answer: D

The strength of our 300-320 dumps is the constant update that we perform to keep abreast with the market trends and changes. Our 300-320 exam question is not only the best option for certification but also enhances your skill to an advance level. More 300-320 new questions (with images) on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDUGlzdWdZNHUwZ28> 2017 Cisco 300-320 exam dumps (All 425 Q&As) from Lead2pass: <https://www.lead2pass.com/300-320.html> [100% Exam Pass Guaranteed]