[Lead2pass New Lead2pass Cisco 400-201 VCE And PDF Instant Download (441-460)

2017 November Cisco Official New Released 400-201 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! 2017 latest released Cisco official 400-201 exam question free download from Lead2pass! All new updated questions and answers are real questions from Cisco Exam Center! Following questions and answers are all new published by Cisco Official Exam Center: https://www.lead2pass.com/400-201.html QUESTION 441What multicast protocols require RP? (Choose two) A. SMB. DMC. SSMD. BiDirE. anything like mLDPAnswer: CD QUESTION 442What is a paradigm of segment routing? A. source routing Answer: A QUESTION 443Which are three characteristics of Cisco Embedded Packet Capture? A. It has the ability to preserve Ethernet encapsulation information when exportedB. It has the ability to capture packets in the Cisco Express Forwarding pathC. It uses EXEC-level commands to start and stop the captureD. The capture can be performed only on physical interfaces and sub-interfaces.E. It has the facility to export the packet capture in pcap formatF. The Cisco IOS output is displayed in a human-readable format Answer: BCE QUESTION 444Which two components does the LDP use to discover neighbors on a network segment? (Choose two) A. 224.0.0.1 multicast addressB. 224.0.0.14 multicast addressC. 711 udp portD. 224.0.0.2 multicast addressE. 646 tcp portF. 711 tcp portG. 646 udp port Answer: DG QUESTION 445Which option is the Cisco cloud management platform that is designed for enterprise and public sector IT organizations to help build private and hybrid clouds? A. cisco intelligent automation for cloudB. cisco ucs directorC. cisco cloud orchestratorD. cisco intercloud fabric Answer: A Explanation: http://blogs.cisco.com/datacenter/introducing-cisco-intelligent-automation-for-cloud-4-0 QUESTION 446Drag and Drop QuestionDrag and drop the QoS characteristics on the left onto its correct QoS mechanism on the right. Answer: QUESTION 447Drag and Drop Question Answer: QUESTION 448Which feature allows an MPLS TE Tunnel to be used by an IGP at the headend of the tunnel: A. MPLS TE link managementB. MPLS TE autoroute announceC. generalized MPLSD. MPLS TE Forwarding AdjacencyE. Differentiated Service TE Answer: B QUESTION 449Which statement about LDP session protection and ldp-igp sync is true: A. both LDP feature can't be used at the same time in MPLS LDP networkB. ldp-igp sync re-exchanges label info when a down-up event occurs, keep the adjacency info in down-up eventC. ldp section protection sync re-exchanges label info when a down-up event occurs, keep the adjacency info in down-up eventD. both ldp feature must be used together to increase fast convergence on mpls ldp network Answer: D QUESTION 450Which option describes a service function as defined in SDN? A. a virtual serverB. a virtual deviceC. a virtual chainD. a virtual network function Answer: D QUESTION 451Refer to exhibit. Customer reported internet stop working for a few times, and it occurred when ASBR1 router reloaded and ospf convergence faster than BGP, which command will solve the issue? A. graceful restartB. bfd min rx 100 max rx 100 multiplier 3C. max-metric router lsa on startup 300D. set overload bit on startup wait for bgp Answer: C QUESTION 452Which two characteristics of GMPLS are true? (Choose two) A. LMP can be used by the natively photonic switches network element type onlyB. The LSP is established directionally through only one signaling messageC. The control channel can terminate on different node types that bearer channels spanD. Two light paths traversing the same fiber link can share the same wavelength on that linkE. OXCs manipulate wavelength that bear the label implicitly Answer: BE QUESTION 453Drag and Drop QuestionDND Multicast VPN, Arrange the steps on the left in order of how the P2MP TE traffic is forwarded across the network. Answer: QUESTION 454What are the improvements in SNMPv3 regarding security? A. authentication and privacyB. its administration offers logical contextsC. view-based access controlD. remote configuration. Answer: ABCD QUESTION 455Specify the label modes for rsvp-te: A. - control method (like ordered or independent)B. - distribution mode (like downstream on demand or unsolicited)C. - retention mode (like conservative or liberal) Answer: ABC QUESTION 456A service provider engineer enabled the BGP next-hop tracking feature and also turned the OSPF to increase the network convergence in case of network failures. However, the operator engineer notices that in case of PE failure, the network convergence is still slow. Which configuration must the operator use to remedy this failure scenario? A. router ospf 1no default-information originatetimer throttle lsa all 1 5 5000timer throttle spf 1 5 5000B. router bgp 65000address-family ipv4no bgp nexthop trigger enablebgp additional-paths install! address-family vpnv4no bgp nexthop trigger enablebgp additional-paths installC. router bgp 65000address-family ipv4bgp nexthop trigger delay 1!address-family vpnv4bgp nexthop trigger delay 1D. router ospf 1default-information originate always metric-type 1timer throttle lsa 1 5 5000timer throttle spf 1 5 5000E. ip prefix-list PREFIX_32 permit 0.0.0.0/0 ge 32!route-map ONLY_32 permit 10match ip address prefix-list PREFIX_32match source-protocol ospf!router bgp 65000address-family vpnv4bgp nexthop route-map ONLY_32 Answer: C QUESTION 457There was also another question for which the answer was prefix prioritization. A. prefix prioritization. Answer: A QUESTION 458A Corporate ABC located in the US acquired Company XYZ, which is located in Europe. Both companies are connected to the internet using their local ISP. A management VLAN must be built

using subnet 192.168.1.0/24 across the ABC and XYZ.Which solution meets this requirement? A. VPLSB. ATOMC. Layer 3 VPND. L2TPv3 Answer: D QUESTION 459In a L2VPN service, customer CE1 sends frames to PE1 using a CoS marking value of 3. However, the remote CE2 receives those frames from PE2 with a CoS marking value of 0. Which description of this behavior is true? A. Egress PE2 is not configured with an outbound policy-map facing CE2 to preserve the customer CoS markingB. Egress PE2 is not configured with mpls ldp explicit-null commandC. Ingress PE1 is remarking the CoS frame received from CE1 with value of 0.D. Egress PE2 is marking EXP 0 upon label imposition. Answer: C QUESTION 460The service provider has the following VPLS requirements. A PE must learn dynamically remote PEs that are members of the same VPLS domain. The VPLS signaling must be in a point-to-multipoint fashion way according to RFC 4761 (Kompella). Which feature must be enabled to meet these requirements? A. LDP signalingB. BGP signalingC. RSVP signalingD. RSVP auto discoveryE. LDP auto discovery Answer: BExplanation:RFC 4761Virtual Private LAN Service (VPLS)Using BGP for Auto-Discovery and Signaling Lead2pass offers the latest Cisco 400-201 exam questions and answers in PDF & VCE. We promise 100% 400-201 exam pass or full money back (Have a try- If success, you will get a high pay job! Failed, nothing, money back!)! We provide instant download of our 400-201 dumps after payment so you can study earlier than others! 400-201 new questions on Google Drive: https://drive.google.com/open?id=0B3Syig5i8gpDMExNMWJIYTIIcUU 2017 Cisco 400-201 exam dumps (All 647 Q&As) from Lead2pass: https://www.lead2pass.com/400-201.html [100% Exam Pass Guaranteed]