

[Lead2pass New Lead2pass Free 200-355 Exam Dumps With PDF And VCE Download (261-280)]

2017 October Cisco Official New Released **200-355** Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! Lead2pass 200-355 braindumps including the exam questions and the answer, completed by our senior IT lecturers and the Cisco product experts, include the current newest 200-355 exam questions. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/200-355.html>

QUESTION 261 An 802.11g network is experiencing intermittent signal degradation and Spectrum Analyzer is being used to try and locate the problem. What two interferers would likely be identified? (Choose two.) A. multiple cell phones B. microwave oven C. FM Radio D. cordless phone E. document scanner Answer: BD

QUESTION 262 A wireless bridge is being installed near an airport. An organization informs the city council about complying with max power levels that could be used and settings on any 5GHz channels used that might interfere with the airport radar. What organization is this? A. Institute of Electrical and Electronics Engineers B. Internet Engineering Task Force C. Federal Communications Commission D. Wireless Fidelity Alliance Answer: C

QUESTION 263 An installation uses a 21dBi parabolic dish. It is connected to the 802.11n radio via low loss antenna coax rated at 4dB loss/100 feet. After testing, it has been determined that 2mW of power will be lost in the cable. An EIRP producing 200mW is desired. What should the transmit power be set to? A. 8mW B. 3dBm C. 3.16mW D. 5mW Answer: C

QUESTION 264 An engineer is seeing a pattern closest to that of an Isotropic Radiator. What other antenna will produce a similar pattern? A. 5 dBi patch B. 13.5 dBi Yagi C. 2.2 dBi omni D. 21 dBi parabolic Answer: C

QUESTION 265 When using multiple SSIDs on a lightweight AP, how does the traffic of each SSID reach the 802.3 network? A. provide routing between them at the core so that the SSIDs can reach the internet B. configure 802.11q trunking on the Ethernet switch port that is connected to the APC. C. configure ACLs at the switch port that will allow all desired SSIDs to pass traffic D. configure the SSIDs on the WLC and it will regulate the traffic based on traffic type Answer: B

QUESTION 266 Refer to the exhibit. Based on the diagram, what two design requirements must be met? (Choose two.) A. WGB is Autonomous B. WGB is Universal C. WGB can be Autonomous or Universal D. Upstream AP is Aironet E. Upstream AP is not Aironet F. Upstream AP can be any make/model Answer: AD

QUESTION 267 What 802.1x role is responsible for moving a port to the authorized state? A. Supplicant B. Authenticator C. Authentication Server D. RADIUS Server Answer: B

QUESTION 268 How many types of control frames are only used in PCF mode? A. 0 B. 1 C. 2 D. 3 E. 4 F. 5 Answer: D

QUESTION 269 An engineer is gathering information for a wireless survey of a hospital. What three pieces of information must be collected for an active survey to assess the outcome best suited for the facility? (Choose three.) A. presence of microwave ovens B. number of patients that are at the facility C. utilization of Location Services or voice applications D. floor plans of adjacent facilities E. use of wireless for secure records F. spectrum analysis to locate all the computer work stations G. existing Network Switch types and model numbers H. type of devices present on the new wireless network Answer: ACH

QUESTION 270 A company wants to implement wireless in all 20 remote office locations and wants centralized management of these remote sites. What application would meet the requirements? A. Control And Provisioning of Wireless Access Points B. Cisco point-to multi-point wireless bridging C. Cisco autonomous access points in FlexConnect mode D. Split MAC architecture utilizing LWAPP and WLC Answer: D

QUESTION 271 A customer mounted three new APs in a small business. After configuring the IP address, users still could not access the web through the new access points. What two configurations are needed to fix this? (Choose two.) A. Security parameters B. Gateway address C. Service Set ID D. Antenna option E. EAP Authentication F. Unique AP Name Answer: BC

QUESTION 272 A client is deploying lightweight APs. Those with LAN connections to the controller would be considered what mode of deployment, while access points deployed across a higher latency connection are deployed in what mode? A. H-REAP; Bridge B. Local; Bridge C. H-REAP; Flex Connect D. Local; Flex Connect Answer: D

QUESTION 273 When using DHCP option 43, the discovery option supports vendor specific identifiers in order to obtain what IP address? A. core router's gateway B. closest distribution switch C. local WLAN controller D. local Radius Server Answer: C

QUESTION 274 Wireless clients are experiencing loss of connectivity while roaming between controllers. To fix this, what configuration should be the same on all controllers within the mobility group? A. management interface IP address B. IP address of the virtual interface C. AP Manager interface IP address D. IP address of the Service Port Answer: B

QUESTION 275 What is a function of the service port on a WLC? A. controls mobility manager communications on all physical ports B. controls out-of-band management for system recovery and maintenance C. controls communication with Cisco Aps D. controls communications for all physical ports Answer: B

QUESTION 276 What are three functions of RRM? (Choose three.) A. dynamic channel assignment B. detection and avoidance of interference C. dynamic antenna polarization D. dynamic transmit power control E. dynamic controller selection F. detection and avoidance of AP client load Answer: ABD

QUESTION 277 What three components are required to configure

Mobility Group Members between Wireless LAN Controllers? (Choose three.) A. Controller Management IP AddressB. Controller Virtual IP AddressC. Controller Multicast IP AddressD. Controller MAC AddressE. Controller Mobility Group NameF. Controller AP Management IP AddressG. Controller RF Group Name Answer: ADE QUESTION 278What authentication method requires a certificate on both the client and authentication server? A. PEAPB. EAP-TLSC. EAP-FAST D. WPA-PSKE. WEPF. EAP-TTLS Answer: B QUESTION 279An enterprise needs their iPhones to connect to the EAP-TLS network. How should the devices be configured? A. push profile and certificate through Configuration UtilityB. configure directly through Settings applicationC. email certificate to device then configure through Settings applicationD. download certificate from web page then configure through Settings applicationE. push profile and certificate through iTunes Answer: A QUESTION 280What AnyConnect module can be used to provide a detailed scan list of the Wi-Fi environment? A. DARTB. TelemetryC. Web SecurityD. NAME. Posture Answer: A If you use Lead2pass braindump as your 200-355 exam prepare material, we guarantee your success in the first attempt. Lead2pass 200-355 dump provides you everything you will need to take your 200-355 Exam. 200-355 exam dumps,200-355 exam question,200-355 pdf dumps,200-355 vce dumps,200-355 braindumps,200-355 study guide, 200-355 practice test, Lead2pass 200-355 **200-355** new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDd3NzLWRUUTRLME0> 2017 Cisco **200-355** exam dumps (All 500 Q&As) from Lead2pass: <https://www.lead2pass.com/200-355.html> [100% Exam Pass Guaranteed]